

DRY CHEMICAL

Automatic Heat Actuated Multi-Purpose



STRIKE FIRST
FIRE EXTINGUISHERS



**WHEN
SECONDS
COUNT.**



Built Tough and Ready to Serve

- Steel cylinder complete with protective skirt
- Super durable polyester powder paint finish with superior corrosion resistance
- UL Listed Heat Activated Sprinkler Head, rated at 165 degrees F (74° Celsius)
- Meets D.O.T. Requirements
- Designed to provide supplementary fire protection
- Available in two mounting styles: horizontal and vertical
- Disposable unit, does not require maintenance and inspection at 6 or 12 years
- Typical installation locations: specific fire risk areas such as flammable liquid storage rooms, construction trailers and manufacturing process areas i.e. paint booths

STRIKE FIRST Automatic Heat Actuated Multi-Purpose Fire Extinguishers are designed for:



A WOOD
PAPER
& CLOTH



C ELECTRICAL
CONDUCTIVITY



B FLAMMABLE
LIQUIDS
& GASES



Manufacturing Fire Equipment for over 35 Years



| CAPACITY | 2.5 lbs (1.13 kg) | 5 lbs (2.3 kg) | 10 lbs (4.5 kg) | 20 lbs (9.1 kg) |
|--|------------------------------------|------------------------------------|------------------------------------|------------------------------------|
| Model No. | SF-AFE2.5ABCV | SF-AFE5ABCV | SF-AFE10ABCV | SF-AFE20ABCV |
| Ship Weight | 5 lbs (2.3 kg) | 8 lbs (3.6 kg) | 17 lbs (7.7 kg) | 32 lbs (14.5 kg) |
| Operating Pressure | 100psi (689 kPa) | 100psi (689 kPa) | 195psi (1344 kPa) | 195psi (1344 kPa) |
| Storage Temperature Range | -65°F to 120°F (-54°C to 490°C) | -65°F to 120°F (-54°C to 490°C) | -65°F to 120°F (-54°C to 490°C) | -65°F to 120°F (-54°C to 490°C) |
| Unit Length | 17.5" (44.4 cm) | 17" (43.2 cm) | 22" (55.8 cm) | 24.5" (62.2 cm) |
| Unit Width | 3.2" (8.13 cm) | 4.25" (10.8 cm) | 5" (12.7 cm) | 7.2" (18.3 cm) |
| Max. Total Flood Volume | 120 ¹³ | 180 ¹³ | 1,300 ¹³ | 2,184 ¹³ |
| Max. Local Application Coverage Area | 4' x 4' | 4' x 6' | 10' x 10' | 12' x 13' |
| Max. Height Above Hazard – Local Application | 4' | 4' | 4' | 4' |
| Max. Height Above Hazard – Flood Application | 7.5' | 7.5' | 13' | 14' |
| Bracket (available separately) | UP2 | HDVB-1 | HDVB-2 | HDVB-3 |

| CAPACITY | 2.5 lbs (1.13 kg) | 5 lbs (2.3 kg) | 10 lbs (4.5 kg) | 20 lbs (9.1 kg) |
|--|------------------------------------|------------------------------------|------------------------------------|------------------------------------|
| Model No. | SF-AFE2.5ABCH | SF-AFE5ABCH | SF-AFE10ABCH | SF-AFE20ABCH |
| Ship Weight | 5 lbs (2.3 kg) | 8.6 lbs (3.9 kg) | 16.5 lbs (7.5 kg) | 32 lbs (14.5 kg) |
| Operating Pressure | 100psi (689 kPa) | 100psi (689 kPa) | 195psi (1344 kPa) | 195psi (1344 kPa) |
| Storage Temperature Range | -65°F to 120°F (-54°C to 490°C) | -65°F to 120°F (-54°C to 490°C) | -65°F to 120°F (-54°C to 490°C) | -65°F to 120°F (-54°C to 490°C) |
| Unit Length | 15" (38.1 cm) | 14.5" (36.8 cm) | 19.5" (49.5 cm) | 22" (55.8 cm) |
| Unit Width | 5.3" (13.4 cm) | 5.8" (14.7 cm) | 6.3" (16 cm) | 7.2" (18.2 cm) |
| Max. Total Flood Volume | 120 ¹³ | 180 ¹³ | 1,300 ¹³ | 2,184 ¹³ |
| Max. Local Application Coverage Area | 4' x 4' | 4' x 6' | 10' x 10' | 12' x 13' |
| Max. Height Above Hazard – Local Application | 4' | 4' | 4' | 4' |
| Max. Height Above Hazard – Flood Application | 7.5' | 7.5' | 13' | 14' |
| Bracket (available separately) | UP2 | HDVB-1 | HDVB-2 | HDVB-3 |



STRIKE FIRST
FIRE EXTINGUISHERS

777 Tapscott Road
Scarborough
Ontario, Canada M1X 1A2

P 416 299-7767
TF 1 888 575-1132

F 416 299-8039
TF 1 888 575-1134

info@strike-first.com | www.strike-first.com